

MAINTENANCE-FREE MOTORCYCLE BATTERY


HPG4A-3 (12V4.0Ah)











GENERAL FEATURES

- Longer lifespan
- · Lower self-discharge
- Totally Maintenance-free
- · Shipped pre-charged and ready to install

*Values are subject to variation of +/- 5% in normal manufacturing processes.


Leoch International Technology Ltd.

Leoch Batteries Pte Ltd



Item		Specifications
Nominal Voltage		12V
Nominal Capacity (10HR)		4.0Ah
Cold Cranking Perfo	rmance Amps@0°F (-18°C)	55A
Dimension (±2mm)	Length	120mm (4.72inches)
	Width	70mm (2.76inches)
	Container Height	92mm (3.62inches)
	Total Height	92mm (3.62inches)
Battery (with acid)	Approx Weight	1.59kg (3.50lbs)
Terminal type		Д
Battery type	HPG Series	
Voltage Full Charge	Constant-Voltage Charge:	
	Initial charging current	Less than 0.3C10
	14.40V~15.00V at 25°C (77°F)	
	Charging time	15~18h
	Constant-Current Charge:	
	Charging current 0.1C ₁₀ , when charging voltage up to 14.40V, continue to charge 4h	
Floating Charge Voltage	Initial charging current	Unlimited
	13.50V~13.80V at 25°C (77°F)	
Capacity affected by Temperature	40°C (104°F)	106%
	25°C (77°F)	100%
	0°C (32°F)	86%
	-15°C (5°F)	65%

Discharge Characteristics (25°C, 77°F)



Leoch Battery Corporation

Leoch Europe S.A.

Data above is recommended and the picture is only for battery effect display, Leoch reserve the final right of explanation. © LEOCH. All rights reserved. Trademarks and logos are the property of LEOCH and its affiliates unless otherwise noted. Subject to revisions without prior notice. E&OE.

Publication No.:LB-HPG4A-3-PD-EN-V1.0-20241112