

MAINTENANCE-FREE MOTORCYCLE BATTERY


HPGU1-4-P (12V25Ah)














GENERAL FEATURES

- Maintenance-free
- · Sealed and non-spillable AGM battery
- · Shipped pre-charged and ready to install

*Values are subject to variation of +/- 5% in normal manufacturing processes.


Leoch International Technology Ltd.

Leoch Batteries Pte Ltd



Item		Specifications
Nominal Voltage		12V
Nominal Capacity (10HR)		25Ah
Cold Cranking Perfo	rmance Amps@0°F (-18°	°C) 320A
Dimension (±2mm)	Length	195mm (7.68inches)
	Width	125mm (4.92inches)
	Container Height	156mm (6.14inches)
	Total Height	176mm (6.93inches)
Battery (with acid)	Approx Weight	8.34kg (18.4lbs)
Terminal type		G
Battery type	Factory Activated Series	
Full Charge	Constant-Voltage Cha	•
	Initial charging current	
	Voltage	14.40V~15.00V at 25°C (77°F)
	Charging time	15~18h
	Constant-Current Cha	irge:
	Charging current $0.1C_{10}$, when charging voltage up to 14.40V, continue to charge 4h	
Floating Charge	Initial charging current	Unlimited
	Voltage 13.50V~13.80V at 25°C (77°F)	
Capacity affected by Temperature	40°C (104°F)	106%
	25°C (77°F)	100%
	0°C (32°F)	86%
	-15°C (5°F)	65%

Discharge Characteristics (25°C, 77°F)



Leoch Battery Corporation

Leoch Europe S.A.

Data above is recommended and the picture is only for battery effect display, Leoch reserve the final right of explanation. © LEOCH. All rights reserved. Trademarks and logos are the property of LEOCH and its affiliates unless otherwise noted.Subject to revisions without prior notice. E&OE.

Publication No.:LB-HPGU1-4-P-PD-EN-V1.0-20241112