

MAINTENANCE-FREE MOTORCYCLE BATTERY

EB12-4-P (12V11Ah)









GENERAL FEATURES

- Maintenance-free
- Sealed and non-spillable AGM battery
- · Shipped pre-charged and ready to install

*Values are subject to variation of +/- 5% in normal manufacturing processes.


Leoch International Technology Ltd.

Leoch Batteries Pte Ltd

CHARACTERISTICS

ltem		Specifications
Nominal Voltage		12V
Nominal Capacity (10HR)		11Ah
Cold Cranking Perfo	rmance Amps@0°F (-18	°C) 180A
Dimension (±2mm)	Length	150mm (5.91inches)
	Width	87mm (3.43inches)
	Container Height	130mm (5.12inches)
	Total Height	130mm (5.12inches)
Battery (with acid)	Approx Weight	3.92kg (8.63lbs)
Terminal type		А
Battery type	Factory Activated Seri	es
Full Charge	Constant-Voltage Charge:	
	Initial charging current	t Less than 0.3C10
	Voltage	14.40V~15.00V at 25°C (77°F)
	Charging time	15~18h
	Constant-Current Cha	irge:
	Charging current $0.1C_{10}$, when charging voltage up to 14.40V, continue to charge 4h	
Floating Charge	Initial charging current	t Unlimited
	Voltage	13.50V~13.80V at 25°C (77°F)
Capacity affected by Temperature	40°C (104°F)	106%
	25°C (77°F)	100%
	0°C (32°F)	86%
	-15°C (5°F)	65%

Discharge Characteristics (25°C, 77°F)



Leoch Battery Corporation

Leoch Europe S.A.

Data above is recommended and the picture is only for battery effect display, Leoch reserve the final right of explanation. © LEOCH. All rights reserved. Trademarks and logos are the property of LEOCH and its affiliates unless otherwise noted. Subject to revisions without prior notice. E&OE.

Publication No.:LB-EB12-4-P-PD-EN-V1.0-20241112