
## MAINTENANCE-FREE MOTORCYCLE BATTERY

EBC12-4 (12V12Ah)







## **GENERAL FEATURES**

- Maintenance-free
- · Sealed and non-spillable AGM battery
- · Shipped pre-charged and ready to install

\*Values are subject to variation of +/- 5% in normal manufacturing processes.


Leoch International Technology Ltd.

Leoch Batteries Pte Ltd



Item		Specifications
Nominal Voltage		12V
Nominal Capacity (10HR)		12Ah
Cold Cranking Perfo	rmance Amps@0°F (-18°	°C) 180A
Dimension (±2mm)	Length	150mm (5.91inches)
	Width	87mm (3.43inches)
	Container Height	130mm (5.12inches)
	Total Height	130mm (5.12inches)
Battery (with acid)	Approx Weight	3.60kg (7.94lbs)
Terminal type		A
Battery type	Factory Activated Serie	es
Full Charge	Constant-Voltage Charge:	
	Initial charging current	Less than 0.3C10
	Voltage	14.40V~15.00V at 25°C (77°F)
	Charging time	15~18h
	Constant-Current Cha	rge:
	Charging current $0.1C_{10}$ , when charging voltage up to 14.40V, continue to charge 4h	
Floating Charge	Initial charging current	Unlimited
	Voltage 13.50V~13.80V at 25°C (77°F)	
Capacity affected by Temperature	40°C (104°F)	106%
	25°C (77°F)	100%
	0°C (32°F)	86%
	-15°C (5°F)	65%

## Discharge Characteristics (25°C, 77°F)



Leoch Battery Corporation

Leoch Europe S.A.

Data above is recommended and the picture is only for battery effect display, Leoch reserve the final right of explanation. © LEOCH. All rights reserved. Trademarks and logos are the property of LEOCH and its affiliates unless otherwise noted. Subject to revisions without prior notice. E&OE.

Publication No.:LB-EBC12-4-PD-EN-V1.0-20250329