


Residential Energy Storage Battery (Rack-mounted)



LR51.2-50



Compact Size

Minimum the footprint



Eco-Friendly

Clean energy



Long Lifespan

Sustainable long cycles



Built-in BMS

Charge & discharge protection

Product Introduction



Up to 40 groups of parallel connections,
flexible capacity expansion



Compatible with mainstream inverters in the
market, providing more options



LED display for voltage, current, temperature,
convenient for users to query



Built-in BMS provides multiple protection
functions

Residential Energy Storage Battery (Rack-mounted)



Item	Parameters
Model	LR51.2-50
Rated Capacity (5HR)	50 Ah
Nominal Voltage	51.2V
Energy	2.56KWh
Discharge Ending Voltage	43.2 V
Charging Limited Voltage	57.6V
Max. Charge/Discharge Current	50 A
Weight	Approx. 28 Kg
Display	With display screen
Protocol	RS485/RS232/CAN
Max number of parallel connections	40
Dimensions (W*D*H) mm (inches)	442 *442 *132
Design life	More than 15 years
Cycle Life	More than 3500 cycles @ 100% DOD
IP Class	IP31
Case Material	SPCC
Operating Temperature	Charging: 0 to +45°C Discharging: -10 to +55°C Storage: -20 to +60°C